



PARKING SUMMARY

1. # OF PARKING SPACES REQUIRED FOR EXISTING SANCTUARY: 250 SEATS / 4 = 63 SPACES (GRASS)
2. # OF PARKING SPACES REQUIRED FOR PROPOSED SANCTUARY: 308 SEATS / 4 = 77 SPACES
3. REQUIRED NEW PAVED PARKING SPACES: = 14 SPACES
4. # OF EXCESS GRASS PARKING SPACES: 0 SPACES
- TOTAL PROVIDED PARKING: = 77 SPACES
5. NEW ADA SPACES: 8 SPACES (INCLUDED IN # 3)
6. ADDITIONAL NEW MOTORCYCLE SPACES: 4 SPACES

PLANTING NOTES:

- (1) Ground cover shall be provided throughout the buffer area. If grass is used, it shall be of a species normally grown as permanent lawns in the vicinity of Palatka, Florida. Grass areas may be sodded, plugged, sprigged or seeded.
- (2) Understory tree species shall be a minimum of five feet in height and have a caliper of at least 1 1/2 inches immediately after planting. Species used shall have an average mature crown spread of at least 15 feet when grown in Palatka, Florida.
- (3) Shrubs and ornamental grasses shall be a minimum of 12 inches in height when measured immediately after planting.
- (4) Shrubs or ornamental grasses planted to form hedges shall be an evergreen species and a minimum of 18 inches in height when measured immediately after planting. Shrubs and ornamental grasses planted to form hedges shall be planted no further apart than 30 inches on center.
- (5) All plantings that die or are destroyed within two years must be replaced.
- (6) To achieve a more natural appearance, plantings should not be evenly spaced or planted in a straight line. Plantings shall be distributed throughout the length of the buffer.
- (7) Plantings shall be installed to current nursery industry standards. Plant materials shall be properly supported to ensure survival. Support devices such as guy wires or stakes shall not interfere with vehicular or pedestrian movement and shall be removed after 12 months.
- (8) The buffer shall provide for the placement of topsoil of a depth sufficient to ensure plant survival.
- (9) To ensure that plants will survive the critical establishment period when they are most vulnerable due to lack of watering, all buffer areas should be provided with means of providing water with one of the following two options: a permanent built-in irrigation system; or a temporary watering system (hoses, water tank truck, etc.) which provides sufficient water to ensure that selected plant species can survive adequately on their own once established.
- (10) All required buffer areas shall be protected from potential damage by adjacent uses and development, including parking and storage areas. A tree protection device shall be installed at the dripline of the tree canopy to protect the tree and root zone

NOT RELEASED FOR CONSTRUCTION

<p>HILLCREST BAPTIST CHURCH - BUILDING & PARKING LOT ADDITION 2009 PRESIDENT STREET - PALATKA, FL</p>	<p style="text-align: center;">SITE PLAN</p>
<p>THE JOHN STOKES COMPANY (904) 321-1832 2424-A LYNNDALE ROAD FERNANDINA BEACH, FLORIDA</p>	<p>WILLIAM E. (ED) TULLY III, INC. Consulting Civil Engineer FLORIDA REG. P.E. # 36191 (904) 824-6371; Fax: (904) 824-9305 10625 Quail Ridge Drive - Ponte Vedra, FL 32081 Certificate of Authorization # 4576 FLA. CERTIFICATION NO. CGC026018</p>
<p>Date 02-01-12 Scale 1"=40' Drawn WES Checked By WET Job 11-011 Sheet 1</p>	<p style="text-align: center;">1</p>